

General Description:

Reve Beton wallpaper is a PVC wall covering on a non-woven backing, designed for inkjet printing.

Available Texture:

Reve Beton Wallpaper

Backing Grammage:	60 +/-20 g/m ²
PVC Grammage:	290 +/-20 g/m ²
Total Grammage:	350 +/-20 g/m ²

Dimensions (depending on the texture):

- 1300mm x 50m
- 1360mm x 50m
- 1370mm x 30m

Type of Printing:

- Solvent, Eco Solvent, Latex, UV

Wash Resistance (before printing):

According to EN 259-2 standard

- **General information:** A digitally printed wallpaper can be washed. Light or moderate stains can be removed with a mild detergent and a damp cloth. Intensive scrubbing of the material is not recommended. It is important to wipe the wallpaper with a damp cloth in a vertical motion (top to bottom) to avoid soaking the edges. Do not use bleach or similar agents.

Chemical Resistance (before printing):

Resistant to: soap, detergents, alcohol, ammonia, alkaline compounds, and diluted acids

Not resistant to: solvents (such as ketones), organic chemical compounds, or aromatic hydrocarbons

Safety / Ecology:

- The material is classified as safe in accordance with: DIN 52900 & 91/155/EEG, 2001/58/EC

Fire Resistance (flammability rating):

Class:	B s1 d0
Euro	
Class 0 / 1	BS 476 Part 6/7
M1	
Class: B1	NF P 92501 / 92507 DIN 4102 – 01*
ABP Number: P-MPA-E-04-507	

Light Resistance:

- 7 out of 8 - International Wool Scale BS EN 20105 / ISO 105-B02